



Светильник линейный архитектурный AL-16100-2 RGB (16 pix) DC12V/12W 48шт x SMD5050/IP65

Артикул AL-16100-2 RGB (16 pix)

В наличии

2 шт.

Склад Красноярск

1 шт.

Склад Кемерово

1 шт.

Характеристики

Производитель SignImpress

Signimpress

LED linear light

AL-16100

- High quality aluminum shell, surface anodic oxidation process, lightweight but high strength.
- Superior light source chip, long lifespan, high luminous efficiency.
- High quality and high thermal conductivity alloy PCB with excellent thermal conductivity and high temperature coefficient.
- Mid-ray white PC lens covers with light emission protection.
- Private control can be achieved by DMX512 Technology.

RoHS CE ENEC



Product specification


Basic parameters		Optical parameters	
Color Temperature	Warm white 3000K/4000K	Beam diameter (mm)	160mm
Rated power	12W/12W	CRI	80
LED number	96/96	Luminous efficiency	45-170lm/W
LED light source	SMD 5050	Application parameters	
Beam angle	120°/120°	Mounting mode	IP65
ELC	RoHS Level III	Working voltage	4V-16V
Anti-plasma halogenated	30	Working temperature	-15°C-35°C
Life span	15000	Weight	150g
Input voltage	DC	Transmission	60%
Output voltage	4000mV	Structure parameters	
Control Method	remote control (DMX512)	Height	12mm
Beam	0.14	Mounting of fixture	800mm standard distance
Mechanical parameters		Case material	Al
Material	Aluminum	Length	1000mm
Beam diameter	16mm	Width	27mm
Weight	150g	Height	12mm
Input power	12W		
Output power	12W		
Control type	DMX		

Note: Reference data are based on ROHS value requirements. Others will be subject to actual value.

DIMENSION



LIGHT DISTRIBUTION CURVE



INSTALLATION METHOD

